



DECLARATION OF PERFORMANCE

No.GEO.001CPR2013-07-01

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $E_b > 10\%$
2. Intended use(s)
For internal wall finishes
3. Name or registered trade mark, and contact address of the manufacturer
GEOTILES, S.L.U.
Carretera Vila-real – Onda, Km 6
12540 Vila-real (Castellón) SPAIN
4. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
5. Name and identification number of notified laboratory, if relevant – *not applicable*
Task(s) carried out
AVCP system
Document issued and date of issue
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C1	>0,5 N/mm²	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Pedro Vilar (Manager)
Name and function

Vila-real, 01-01-2021
Place and date of issue

geotiles S.L.U.
Ctra. Vila-real – Onda, Km 6
12540 VILA-REAL (Castellón) ESPAÑA
B12484784
Signature



DECLARATION OF PERFORMANCE

No.GEO.002CPR2013-07-01

- Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $3\% < E_b \leq 6\%$
- Intended use(s)
For internal floorings
- Name or registered trade mark, and contact address of the manufacturer
GEOTILES, S.L.U.
Carretera Vila-real – Onda, Km 6
12540 Vila-real (Castellón) SPAIN
- System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
- Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
- Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 000 N	
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Pedro Vilar (Manager)
Name and function

Vila-real, 01-01-2021
Place and date of issue


geotiles S.L.U.
Signature
Ctra. Vila-real - Onda, Km. 6
12540 VILA-REAL (Castellón) ESPAÑA
B12424784



DECLARATION OF PERFORMANCE

No.GEO.003CPR2013-07-01

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with low water absorption $E_b \leq 0,5 \%$
2. Intended use(s)
For internal and external, floorings and wall finishes
3. Name or registered trade mark, and contact address of the manufacturer
GEOTILES, S.L.U.
Carretera Vila-real – Onda, Km 6
12540 Vila-real (Castellón) SPAIN
4. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
5. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}/A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 300 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	> 1 N/mm²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Pedro Vilar (Manager)
Name and function

geotiles S.L.U.
Ctra. Vila-real – Onda, Km. 6
12540 VILA-REAL (Castellón) ESPAÑA
B12424784
Signature

Vila-real, 01-01-2021
Place and date of issue



DECLARATION OF PERFORMANCE
No.GEO.004CPR2013-07-01

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $0,5\% < E_b \leq 3\%$
2. Intended use(s)
For internal floorings
3. Name or registered trade mark, and contact address of the manufacturer
GEOTILES, S.L.U.
Carretera Vila-real – Onda, Km 6
12540 Vila-real (Castellón) SPAIN
4. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
5. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 100 N	
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Pedro Vilar (Manager)
Name and function

geotiles s.l.u.
Ctra. Vila-real - Onda, Km. 6
12540 VILA-REAL (Castellón) ESPAÑA
812424784
Signature

Vila-real, 01-01-2021
Place and date of issue



DECLARATION OF PERFORMANCE

No.GEO.005CPR2013-07-01

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with low water absorption $E_b \leq 0,5\%$ with thickness $< 7,5\text{ mm}$
2. Intended use(s)
For internal and external, floorings and wall finishes
3. Name or registered trade mark, and contact address of the manufacturer
GEOTILES, S.L.U.
Carretera Vila-real – Onda, Km 6
12540 Vila-real (Castellón) SPAIN
4. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
5. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 700 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	> 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Pedro Vilar (Manager)
Name and function

Vila-real, 01-01-2021
Place and date of issue

geotiles S.L.U.
Ctra. Vila-real - Onda, Km. 6
12540 VILA-REAL (Castellón) ESPAÑA
812424784
Signature



DECLARATION OF PERFORMANCE

No.GEO.005CPR2013-07-01

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with low water absorption $E_b \leq 0,5\%$ with thickness $< 7,5$ mm
2. Intended use(s)
For internal and external, floorings and wall finishes
3. Name or registered trade mark, and contact address of the manufacturer
GEOTILES, S.L.U.
Carretera Vila-real – Onda, Km 6
12540 Vila-real (Castellón) SPAIN
4. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
5. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	< 0,01 mg/l	
- Lead	< 0,1 mg/l	
Breaking strength	> 700 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2 E S2	> 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Pedro Vilar (Manager)
Name and function

geotiles S.L.U.

Ctra. Vila-real - Onda, Km. 6
12540 VILA-REAL (Castellón) ESPAÑA
B12424784

Signature

Vila-real, 01-01-2023
Place and date of issue